



Declaration of Performance



EN 14967

13

In accordance with Regulation (EU) N° 305/2011;

We the manufacturer:

Icopal Ltd. Barton Dock Road, Manchester, M32 0YL. United Kingdom

Hereby declare the product(s) named below:

Monarfloor BridgeStop Acoustic Membrane

Production location ref: S0001-01-100

Complies with the provisions concerning the attestation of conformity and product performance as described in Annex ZA of the product standard: **EN 14967 :2006 -Flexible sheets for waterproofing - bitumen damp proof courses.**

Description and Use: Modified bitumen membranes with a polyester carrier with silica sand finish, intended for use as a damp-proof course membrane in applications such as walls and floors.

System of assessment of verification of constancy of performance (AVCP): System 3

Determination of the product type on the basis of Initial Type Testing (ITT), type calculation, tabulated values or descriptive documentation of the product under system AVCP 3 was carried out by notified body N°. 0086, BSI Product Services.

DECLARED PERFORMANCE

Essential Characteristic	Performance	Tolerance	Units	Harmonised technical specification
Reaction to fire	Class F	-	-	EN 14967:2006
Watertightness	Pass	-	-	
Resistance to impact	≥300	-	mm	
Resistance to static loading	≥20	-	kg	
Durability against ageing	Pass	-	-	
Resistance to Cold Bend	≤ -15	-	°C	

MD = Machine Direction. TD = Transverse Direction.

Signed for and on behalf of the manufacturer by:

Neil Harrison
Position: Technical Director
Place: Manchester, UK
Date: 18 June 2013

..... (signature)