



**Monarfloor®
Angled Flanking
Band**

Monarfloor® Flanking Band

Acoustic strip designed to reduce sound transmission through timber and concrete floors.

Monarfloor Flanking Band isolates party and flanking walls reducing both impact vibration transmission from the floor and the flanking sound transmission path within the building.

Construction

Flexible 6mm foam band.

Availability

Monarfloor® Flanking Band is available in either standard flat, deep flat, standard angled or deep angled in boxes of 5 of each type.

Features and Benefits

- Flexible band that forms a seal between the structure and acoustic flooring system.
- Easily cut and formed to suit all applications.
- Can be bonded with Monarfloor® High Performance Acoustic Adhesive.
- Offers superior damping and isolation performance



Technical Support

Monarfloor® Acoustic Systems offers FREE technical advice and assistance on all aspects of acoustic systems.

We can also undertake site visits to provide contractors with advice and assistance at every stage of a project from concept to completion.

NOTE: This information is given in good faith being based on the latest knowledge known to Monarfloor® Acoustic Systems. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard terms and conditions of sale, a copy of which is available on request.

FLAT	
Standard	
Size (W x L)	75mm x 2000mm
Thickness	6mm
Deep Flat	
Size (W x L)	150mm x 2000mm
Thickness	6mm

ANGLED	
Standard	
Size (W x L)	75mm x 2000mm
Thickness	6mm
Deep	
Size (W x L)	150mm x 2000mm
Thickness	6mm

Installation at a glance

- Ensure the sub-floor and walls are suitably prepared.
- Flank all perimeter with Monarfloor® Flanking Band.
- Butt the acoustic flooring treatment tight to the Monarfloor® Flanking Band.
- After installing the acoustic flooring system, install skirting and trim off excess Flanking Band.

For full details including advice on services and penetrations refer to our Flanking Band Installation Sheet or visit our website: www.monarfloor.co.uk